#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization

International Bureau





#### (43) International Publication Date 30 June 2005 (30.06.2005)

#### PCT

### (10) International Publication Number WO 2005/059195 A1

(51) International Patent Classification7: C22C 21/02, B21J 5/00

C22F 1/043,

(21) International Application Number:

PCT/JP2004/019460

(22) International Filing Date:

17 December 2004 (17.12.2004)

(25) Filing Language:

**English** 

(26) Publication Language:

**English** 

(30) Priority Data:

2003-421424 18 December 2003 (18.12.2003) JP 60/534,191 2 January 2004 (02.01.2004) US 2004-067154 10 March 2004 (10.03.2004)


(71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).

(72) Inventor; and

- (75) Inventor/Applicant (for US only): OKAMOTO, Yasuo [JP/JP]; c/o Showa Denko K.K., 7840, Nagauchi, Kitakatashi, Fukushima 966-0845 (JP).
- (74) Agents: FUKUDA, Kenzo et al.; Kashiwaya Bldg., 6-13, Nishishinbashi 1-chome, Minato-ku, Tokyo 105-0003 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: METHOD FOR PRODUCING SHAPED ARTICLE OF ALUMINUM ALLOY, SHAPED ALUMINUM ALLOY AR-TICLE AND PRODUCTION SYSTEM



(57) Abstract: A method for producing an aluminum-alloy shaped product, includes a step of forging a continuously cast rod of aluminum alloy serving as a forging material, in which the aluminum alloy contains Si in an amount of 10.5 to 13.5 mass%, Fe in an amount of 0.15 to 0.65 mass%, Cu in an amount of 2.5 to 5.5 mass% and Mg in an amount of 0.3 to 1.5 mass%, and heat treatment and heating steps including a step of subjecting the forging material to pre-heat treatment, a step of heating the forging material during a course of forging of the forging material and a step of subjecting a shaped product to post-heat treatment, the pre-heat treatment including treatment of maintaining the forging material at a temperature of -10 to 480°C for two to six hours.

WO 2005/059195 A1 |||||||||||||||||||||||

## WO 2005/059195 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.